

CXDF 24-48/2kW

Cordex™ Series DC-DC Converters



Your Power Solutions Partner

- DC-DC converter supports small to medium 48Vdc loads from legacy 24V power systems
- High power density modular design, up to 2kW output per module
- Advanced monitoring and control capability including remote accessibility
- Internal low voltage shutdown for cost effective integration into existing systems



Cordex DC-DC converters bring advanced technology to the DC power industry. Innovative engineering combines the best in efficiency and reliability meeting a wide array of power requirements. The converter system is a perfect solution for providing 24Vdc output from a standard 48Vdc power system for a variety of dual-voltage system applications including powering of wireless radios.

The fan-cooled CXDF 24-48/2.0kW converter has extremely high density, providing the most power in the least amount of space. Each 19" shelf can accommodate up to 4 compact 2RU modules. The converter system can be controlled and monitored by a central Cordex CXC controller and optionally via a shelf integrated CXCI controller solution for stand alone operation.

Local and remote setup, adjustment and control is a simple single-step process with the Cordex CXC system controller. By utilizing TCP/IP technology, complete configuration and monitoring of power equipment is possible through a network web browser.

CXDF 24-48/2kW Cordex™ Series DC-DC Converters

Part Number: 012-526-20

ELECTRICAL

Input voltage:21 to 30Vdc
Input current:.....Up to 94A @ 24V
Efficiency:.....>88%
Input noise:
 Voice band:<32dBnC
 Wide band:.....<10mV RMS to 10MHz
 <150mVp-p to 100MHz
Output power:2000W max @ -54V
Output voltage:-54Vdc nominal
Output current:37A max
Regulation:-1% +/-0.1% load (static)
 +/- 0.1% line (static)
Output noise:
 Voice band:<38dBnC
 Wide band:.....<10mV RMS to 10MHz
 <150mVp-p to 100MHz
Acoustic noise:<60dBa @ 1m (3ft)

PERFORMANCE / FEATURES

Indicators:Input ok LED (green)
 Output ok LED (green)
 Module fail LED (red)
Adjustments:Via CXC controller
Protection:.....Input fuse
 Input inrush current limit
 Output fuse
 Over temperature limiting
 Input high and low voltage shutdown
 Current limit/short circuit protection
Miscellaneous:.....Control and monitoring via CXC controller
 (requires v1.96 min)
 Low voltage cutoff (LVD)

MECHANICAL

Dimensions:
 mm:.....84H x 100W x 235D
 in:3.3H x 3.94W x 9.25D
Weight:.....2.8kg (6.2lbs)

ENVIRONMENTAL

Temperature:.....-40 to 55°C (de-rated power up to 75°C)
Humidity:0 to 95% NC

SHELVES

24-48V 5-Mod 23" shelf (single input) P/N: 030-900-20
24-48V 4-Mod 19" shelf (single input) P/N: 030-839-20

› Mechanical

24-48V 5-Mod 23" shelf dimensions:
 mm:.....89H x 584W x 304D
 in:3.5H x 23.0W x 12.0D
Weight:.....10.4kg (23.0lbs)

24-48V 4-Mod 19" shelf dimensions:
 mm:.....89H x 438W x 310D
 in:3.5H x 17.2W x 12.2D
Weight:.....8.5kg (19lbs)

› Performance / Features

CAN bus communication
 Optional integrated CXCI controller
 ± Input busbar integration with standard 3.1kW systems (S-mod shelf)

RELATED COMPONENTS

External Options:

567-808-19:.....Kydex cover, 23" CXDF shelf
 567-809-19:Kydex cover, 19" CXDF shelf

AGENCY COMPLIANCE

Safety:.....CSA/UL C22.2 60950 (NRTL)
 CE IEC/EN 60950
 CE marked
EMI:.....Class A radiated
 Class A conducted
 EN 6100-4-2, -3, -4, -6
 GR-1089 (where applicable)
 GR-63



CXDF 24-48/2kW 23", 5-module shelf

Alpha Technologies Ltd.

Canada: Burnaby, British Columbia T: 604.436.5900 F: 604.436.1233
 United States: Bellingham, Washington T: 360.647.2360 F: 360.671.4936

For more information visit www.alpha.ca

#048-726-10 Rev C (07/2016)

Alpha Technologies reserves the right to make changes to the products and information contained in this document without notice.
 Copyright © 2016 Alpha Technologies. All Rights Reserved. Alpha® is a registered trademark of Alpha Technologies.
 member of The Alpha Group™ is a trademark of Alpha Technologies.

member of The  Group™