



an EnerSys® company

Continuity 1000-3000

Convertible Indoor On-line UPS Series



- Feature rich on-line UPS series with rack/tower convertible design and rotating LCD panel enabling easy integration into a wide variety of applications and locations
- Wide input power frequency and voltage window accommodates broad operating range for different working requirements
- Advanced digital control technology achieves higher reliability and greater immunity from utility power problems
- Emergency shutdown control through EPO complies with national safety regulations and local code
- Programmable receptacles enable flexible power backup
- Powerful built-in charger shortens battery charging time and extends runtime
- Hot swappable battery allows replacement without interruption to critical loads

The Continuity 1000-3000 Series, equipped with field-proven Digital Signal Processor, is the ideal UPS system for Servers, Networks, Storage, Telecommunications and Industrial Equipment.

Continuity 1000-3000 Convertible Indoor On-line UPS Series

Nominal Specifications			
Model	Continuity 1000	Continuity 2000	Continuity 3000
120Vac P/Ns*	0170009	0170010	0170011
Input			
Voltage Window:	60~144Vac for 120V system	60~144Vac for 120V system	60~144Vac for 120V system
Frequency:	50/60 ±5% (Auto Sensing)	50/60 ±5% (Auto Sensing)	50/60 ±5% (Auto Sensing)
Phase/Wire:	Single, Line + Neutral + Ground	Single, Line + Neutral + Ground	Single, Line + Neutral + Ground
Power Factor :	>0.99 (Full Load)	>0.99 (Full Load)	>0.99 (Full Load)
Output			
Voltage:	100/110/115/120/127Vac	100/110/115/120/127Vac	100/110/115/120/127Vac
Voltage Regulation:	<±1% until low battery warning	<±1% until low battery warning	<±1% until low battery warning
Capacity:	1000VA/800W	2000VA/1600W	3000/2400W
Wave Form:	Sine Wave, THD<3% (no load to full load)	Sine Wave, THD<3% (no load to full load)	Sine Wave, THD<3% (no load to full load)
Frequency Stability:	±0.1% unless synchronized to line	±0.1% unless synchronized to line	±0.1% unless synchronized to line
Frequency Regulation:	3Hz or 1Hz (Setting by software)	3Hz or 1Hz (Setting by software)	3Hz or 1Hz (Setting by software)
Transfer Time:	0 m sec	0 m sec	0 m sec
Crest Factor:	3:1	3:1	3:1
Efficiency (AC to AC):	>85%	>85%	>88%
Autonomy (80% load):	7.9 mins	7.9 mins	6.5 mins
DC Start:	Yes	Yes	Yes
Battery			
Type:	Sealed Lead Acid Maintenance Free	Sealed Lead Acid Maintenance Free	Sealed Lead Acid Maintenance Free
Capacity:	7Ah	7Ah	9Ah
Quantity:	3	6	6
Voltage:	36Vdc	72Vdc	72Vdc
Recharge Time:	4 hours to 90%	4 hours to 90%	4 hours to 90%
Built-in Charger: (max. charging current)	1.8A	2.1A	2.7A
Protection			
Overload AC Mode & Backup Mode: (delay before switching to bypass)	<105% continuously >106%~120% for 30 seconds transfer to bypass >121%~150% for 10 seconds transfer to bypass	>150% Buzzer continuously alarms • AC mode: immediately transfer to bypass • Backup mode: immediately shutdown	
Bypass Mode:	<105% continuously >106%~120% for 250 seconds shut down >121%~130% for 125 seconds shut down >131%~135% for 50 seconds shut down >136%~145% for 20 seconds shut down >146%~148% for 5 seconds shut down	>149%~157% for 2 seconds shut down >158%~176% for 1 seconds shut down >177%~187% for 0.32 seconds shut down >188% for 0.16 seconds shut down Buzzer continuously alarms	
Overheat:	AC Mode: Switch to Bypass; Backup Mode: UPS shuts down immediately		
Battery Low:	Alarm and Switch Off	Alarm and Switch Off	Alarm and Switch Off
EPO:	UPS shuts down immediately	UPS shuts down immediately	UPS shuts down immediately
Battery:	Advanced Battery Discharge Management (ABDM)		
Noise Suppression:	115V System: 400 Joules	400 Joules	400 Joules

*Consult your Alpha representative for 230Vac P/Ns



an EnerSys® company

Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4
Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364
For more information visit www.alpha.com

© 2021 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.

10/2021
#0480008-00 REV H

Continuity 1000-3000 Convertible Indoor On-line UPS Series

Model	Continuity 1000	Continuity 2000	Continuity 3000	
Display				
LCD:	Normal, Battery, Bypass, Programmable Outlet 1, Programmable Outlet 2, Self-Test, Battery Weak & Bad, Site Wiring Fault, Fault Overload, and Load/Battery Level conditions.			
Key:	On button/Off button (Test/Alarm silence button)			
Self-Diagnostics:	Upon Power On and Software Control			
Communication Slots:	Relay contact board or SNMP card			
Alarms				
Audible & Visual:	Line Failure, Battery Low, Overload, System Fault Conditions			
Mechanical				
Dimensions:	mm:	440W x 88H x 405D	440W x 88H x 650D	440W x 88H x 650D
	inches:	17.3W x 3.5H x 16D	17.3W x 3.5H x 25.6D	17.3W x 3.5H x 25.6D
Input Connector:	5' Line cord with 5-15P		5' Line cord with 5-20P	5' Line cord with L5-30P
Outlets 120Vac:	6 x NEMA 5-15R		2x5-15R + 2 x 5-20R	4x5-15R + 1xL5-30R
Net Weight:	15.1kg (33.3lbs)		27.9kg (61.5lbs)	29.7kg (65.4lbs)
Environment				
Operating Temperature:	0-40°C (32-104°F)		0-40°C (32-104°F)	0-40°C (32-104°F)
Altitude:	0 ~ 1000m/3300ft			
Humidity:	90% RH Maximum, Non-Condensing		90% RH Maximum, Non-Condensing	90% RH Maximum, Non-Condensing
Noise:	<50dB (at 1m/3.3ft)		<50dB (at 1m/3.3ft)	<50dB (at 1m/3.3ft)
Heat Dissipation Watt (BTU/h):	124 (422)		247 (843)	371 (1265)
Computer Interface				
Interface Type:	Standard RS232 and USB		Standard RS232 and USB	Standard RS232 and USB
Communication Slot:	Dry Contact Card or SNMP card		Dry Contact Card or SNMP card	Dry Contact Card or SNMP card
Agency Compliance				
Quality:	ISO 9001 certified manufacturing			
Standard:	UL 1778 and CSA C22.2 107.3			
EMC:	EMC: FCC Class A			
Marks:	UL, cUL			
Battery Pack				
Model	BP Continuity 1000	BP Continuity 2000	BP Continuity 3000	
P/N:	0320004-001	0320005-001	0320006-001	
Battery Type:	7Ah	7Ah	9Ah	
Output Voltage:	36Vdc	72Vdc	72Vdc	
Battery Quantity:	12pcs	12pcs	12pcs	
Unit Weight:	38kg (83.8lbs)	38kg (83.8lbs)	44.6kg (83.8lbs)	
Dimensions:	mm:	88H x 440W x 650D	88H x 440W x 650D	88H x 440W x 650D
	inches:	3.5H x 17.3W x 25.6D	3.5H x 17.3W x 25.6D	3.5H x 17.3W x 25.6D



Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4
 Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364
 For more information visit www.alpha.com

© 2021 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.

Continuity 1000-3000 Convertible Indoor On-line UPS Series

Rack/Tower Design:	<ul style="list-style-type: none"> Enables integration into a wide variety of environments. Optional rack-mount rail available.
Advanced Digital Control Technology:	Achieves higher reliability and greater immunity from Utility power problems to the connected load.
Wide Input Frequency and Voltage Windows:	A wide input frequency window from 45Hz to 65Hz and a voltage input window of 60~144VAC for 120Vac system.
Unity Input Power Factor:	Meets today's industry standard for energy saving and low current harmonic pollution to the Utility.
Double Conversion On-line Technology:	Completely re-generates the Utility Power to correct power disturbances in the Mains. The unit provides clean AC power with VFI (Voltage and Frequency Independent) from the Utility.
User Friendly Display:	An easy-to-read LCD/LED display provides real-time indication of all major system parameters and system status including load level, battery level, bad battery, site wiring fault, overload and programmable outlet for easy service.
Emergency Shutdown Control Through EPO:	Allows users to shut down the UPS completely in an emergency to ensure a safe operating environment.
Powerful Built-in Charger:	Provides approximately 0.3C charging ability to re-charge internal battery to 90% in 3 hours.
Programmable Receptacles:	Remote Reboot and Load Shedding via software reserving back-up power for critical loads.
Hot Swappable Battery:	Allows battery replacement without UPS or critical load interruption.
The Communication Software:	The bundled communication software allows the control of the UPS and graceful shutdown when Utility fails.
Users Can:	<ul style="list-style-type: none"> Remotely test the major operating functions of the UPS Communicate via SNMP/Web/Network adapter Access UPS functions via the Web Alert users via SMS messages against specific events
Customer Options Slot:	<ul style="list-style-type: none"> The Options Slot allows further flexibility in Network configuration. An internal 2nd RS232 card, 2nd USB card, SNMP card or Dry Contact card provide isolated contacts for industrial and remote alarm panel application.
Downloadable Setting Tool:	Voltage Configuration, UPS Mode Selection, Output Voltage Fine Tuning, Bypass Voltage Window, Frequency Synchronized Window and Programmable Outlet Setting can be re-configured by the setting tool.
Extended Runtime Capability:	Enables users to connect additional battery banks by simply plugging in the battery connectors between the UPS and battery banks without requiring additional chargers.
Optional External Bypass Switch:	Ensures continuous supply of power to the critical load in the event of electronic failure, overload, over-temperature, or scheduled maintenance.
RS232 and USB Communication Interfaces:	The advanced technology allows the RS232, USB and SNMP slot to be activated simultaneously.
Super Compact Convertible Design:	With a most compact 2U design, the UPS occupies less space in a 19" rack cabinet. The convertible design enables integration into a wide variety of environments.



Alpha Continuity Tower Configuration



Alpha Continuity Rack Configuration



an EnerSys® company

Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4
 Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364
 For more information visit www.alpha.com

© 2021 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.

10/2021
 #0480008-00 REV H