



PRODUCT CHANGE NOTIFICATION

PCN # 1141107

FlexPoint FPR1207-F Power Supply Product Discontinuation

<p>1. Supplier Information Alpha Technologies, Ltd. 7700 Riverfront Gate, Burnaby, BC V5J 5M4 Canada Contact: Daljit Hothi Associate Product Manager 604 422 4490 daljit.hothi@alpha.ca</p>	<p>2. Product Change Notification Number PCN # 1141107</p>															
<p>3. Issue Date of Change 11/07/2014</p>	<p>4. System and Product Description The FlexPoint FPR1207-F has been discontinued and is replaced by FlexPoint FP1208-F.</p>															
<p>5. New Product ID FlexPoint FP1208-F : 010-353-20</p>	<p>6. Old Product ID FlexPoint FPR1207-F : 010-344-20</p>															
<p>7. Associated Products or Changes Affected FlexPoint FPR1207-F : 010-344-20</p>																
<p>8. Drawing No. N/A</p>	<p>9. Product Change Classification Class B Changes that are made to incorporate improvements in the design of existing products that result in better operation, improved testing and maintenance, longer life, service improvements, operation cost reductions to a customer, and/or addition of new features.</p>															
<p>10. Reason(s) for Change FlexPoint FPR1207-F has been discontinued due to an unexpected component obsolescence in the global supply chain.</p>																
<p>11. Description of Change The FlexPoint FP1208-F is a drop-in replacement for the FlexPoint FPR1207-F. Noticeable differences are as follows:</p> <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 10px;"> <thead> <tr> <th style="width: 35%;"></th> <th style="width: 33%;">FPR1207-F (010-344-20)</th> <th style="width: 32%;">FP1208-F (010-353-20)</th> </tr> </thead> <tbody> <tr> <td>Dims(H" x W" x D")</td> <td style="text-align: center;">7.75 x 8.75 x 3.0</td> <td style="text-align: center;">6.6 x 7.5 x 3.28</td> </tr> <tr> <td>Operating Temperature</td> <td style="text-align: center;">32 to 104°F (0 to 40°C)</td> <td style="text-align: center;">4 to 113°F (-20 to 45°C)</td> </tr> <tr> <td>Output</td> <td style="text-align: center;">12Vdc, 7 Watts</td> <td style="text-align: center;">12Vdc, 8 Watts</td> </tr> <tr> <td>Battery(sold separately)</td> <td style="text-align: center;">7.2Ah or 8Ah</td> <td style="text-align: center;">5.1Ah or 7.2Ah or 8Ah</td> </tr> </tbody> </table>			FPR1207-F (010-344-20)	FP1208-F (010-353-20)	Dims(H" x W" x D")	7.75 x 8.75 x 3.0	6.6 x 7.5 x 3.28	Operating Temperature	32 to 104°F (0 to 40°C)	4 to 113°F (-20 to 45°C)	Output	12Vdc, 7 Watts	12Vdc, 8 Watts	Battery(sold separately)	7.2Ah or 8Ah	5.1Ah or 7.2Ah or 8Ah
	FPR1207-F (010-344-20)	FP1208-F (010-353-20)														
Dims(H" x W" x D")	7.75 x 8.75 x 3.0	6.6 x 7.5 x 3.28														
Operating Temperature	32 to 104°F (0 to 40°C)	4 to 113°F (-20 to 45°C)														
Output	12Vdc, 7 Watts	12Vdc, 8 Watts														
Battery(sold separately)	7.2Ah or 8Ah	5.1Ah or 7.2Ah or 8Ah														

12. Effect of Change Change will have no effect to system operation or usability what is stated in section 11	
13. Material/Product Affected N/A	
14. Documentation Affected N/A	
15. Supplier Implementation Date Orders for FlexPoint FPR1207-F will not be accepted. Customers will be requested to revise PO's to FlexPoint FP1208-F.	16. Modification Completion Date N/A
17. Modification Location N/A	
18. Modification Cost N/A	
19. Location and Quantity of Equipment N/A	
20. Attachments N/A	
21. Comments None	